

UNCLASSIFIED

AD NUMBER	
AD514184	
CLASSIFICATION CHANGES	
TO:	UNCLASSIFIED
FROM:	SECRET
LIMITATION CHANGES	
TO: Approved for public release; distribution is unlimited.	
FROM: Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; DEC 1970. Other requests shall be referred to Rome Air Development Center, Griffiss AFB, NY 13441-5700. This document contains export-controlled technical data.	
AUTHORITY	
RADC ltr dtd 16 Jul 1974; RADC ltr dtd 16 Jul 1974	

THIS PAGE IS UNCLASSIFIED

SECURITY

MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U.S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

SECRET

RADC-TR-71-15
Technical Report
December 1970



HF BACKSCATTER ECHOES FROM WHITE SANDS SPREAD F EXPERIMENT (U)

Sponsored By:
Advanced Research Projects Agency
ARPA Order No. 1057

Principal Investigator: Dr. George Thome
Phone: 617-443-9521

Contract Engineer: J. J. Simons **Project Engineer:** V. J. Coyne
Phone: 315-330-3451 **Phone:** 315-330-3107

Contractor: Raytheon Company
Contract Number: F30602-68-C-0299
Effective Date of Contract: 19 February 1968
Contract Expiration Date: 1 July 1971
Amount of Contract: \$475,621.00
Program Code Number: 1E20

DDC
RECEIVED
MAR 4 1971
A

In addition to security requirements which must be met, this document is subject to special review and is not to be transmitted to foreign governments or foreign persons without prior approval of ARPA/SIS, Arlington, VA 22209.

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws (Title 18, U.S.C., sections 793 and 794), transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

The views and conclusions contained in this document are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Advanced Research Projects Agency or the U.S. Government.

Rome Air Development Center
Air Force Systems Command
Griffiss Air Force Base, New York

DDC CONTROL
NO. 10795

SECRET

When US Government drawings, specifications, or other data are used for any purpose other than a definitely related government procurement operation, the government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded, by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Do not return this copy. When not needed, destroy in accordance with pertinent security regulations.

SECRET

GROUP 1 CONTROLLED ITEM No. 36-610
--

HF BACKSCATTER ECHOES FROM WHITE SANDS SPREAD F EXPERIMENT (U)

G. D. Thome
D. W. Blood

Raytheon Company

In addition to security requirements
which must be met, the document is
subject to special export controls
and is restricted to official
use only. It is not to be
distributed outside the
Department of Defense without
prior approval of the
ASAC/SEC, Arlington VA 22204.

This research was supported by the
Advanced Research Projects Agency
of the Department of Defense and
was monitored by Vincent J. Coyne
RADC (OCSE), GAFB, NY 13440 under
Contract No. F30602-68-C-0299.

UNCLASSIFIED

DOWNGRADED AT 12 YEAR
INTERVALS; NOT AUTOMATICALLY
DECLASSIFIED. DOD DIR 5200.10

SECRET

DDC CONTROL
NO 10795

PUBLICATION REVIEW

This technical report has been reviewed and is approved.



RADC Project Engineer



RADC Contract Engineer

SECRET

ABSTRACT (U)

(S) A series of experiments were run during the period 5-16 October 1970 in which HF radars at the White Sands Missile Range (WSMR) were used to search for direct backscatter from ionospheric irregularities produced by the Boulder heater. The observations were made from White Sands because radars at this location view the heated volume normal to the earth's magnetic field. If the irregularities are field aligned (as might be expected from the similarity between the range spreading seen on Boulder ionograms and that due to the field-aligned irregularities responsible for natural "spread-F") then they will be aspect sensitive and the radar cross-section will be greatest looking normal to the field.

(S) Direct echoes from the heated volume were unquestionably observed. Returns were found at radar frequencies up to 30 MHz (the highest frequency available) at times when the local plasma frequency over Boulder was as low as 5 MHz at the layer peak. These echoes occurred at the expected range and were well correlated in time with the turn-on and turn-off of the heating transmitter. The results varied greatly from day to day for reasons that are not yet understood. When a direct echo was observed it grew continuously while the heater was on and died rapidly when it was turned off (lasting about 10 seconds at 30 MHz and 100 seconds at 13 MHz). Typically the direct returns exhibited doppler spectra a few Hertz wide with a net doppler offset of a few Hertz (at 30 MHz), implying a relative velocity between scatterers of a few tens of meters per second and a net southward drift of comparable magnitude.

(S) The strength and wavelength dependence of the returns (for the one case studied in detail) required a root-mean-square electron density fluctuation of about 12% and a correlation length of about 0.8 meters if the scatterers occupied a

SECRET

SECRET

cylindrical volume 100 kilometers in diameter and 100 kilometers in length, had a Gaussian autocorrelation function, and were isotropic. These requirements are not so severe as to rule out isotropic scatterers and so it can not be concluded that the observed irregularities were field aligned. However much weaker electron density fluctuations and a smaller scattering volume would be required if the scatterers are in fact field aligned. Further measurements will be required to resolve this question.

(S) In addition to direct echoes from the heated volume, perturbations in the ground backscatter returning through the heated volume are also seen. These perturbations are definitely heater related but have received little study as yet.

SECRET

UNCLASSIFIED

CONTENTS (U)

	<u>Page</u>
ABSTRACT (U)	iii
I. <u>INTRODUCTION AND EXPERIMENTAL CONFIGURATION</u> (U)	1
II. <u>OBSERVATIONS AND RESULTS</u> (U)	4
A. <u>Backscatter Range Delay Versus Time Records</u> (U)	4
B. <u>Doppler Spectral Variation with Sample Depth</u> (U)	5
C. <u>Received Power and Spectral Variation with Time</u> (U)	7
D. <u>Power Spectrum of Additional Echoes</u> (U)	7
E. <u>Doppler Distribution Changes with Time</u> (U)	8
III. <u>THEORETICAL CONSIDERATIONS</u> (U)	28
A. <u>Scattering Cross-Section</u> (U)	28
B. <u>Numerical Example</u> (U)	31
IV. <u>SUMMARY AND CONCLUSIONS</u> (U)	34
<u>DISTRIBUTION LIST</u> (U)	38

UNCLASSIFIED

SECRET

I. INTRODUCTION AND EXPERIMENTAL CONFIGURATION (U)

(S) The White Sands Spread-F Experiment was done by Raytheon during Project Ivory Coral over the two week period from October 5 through October 16, 1970. During this time, six ionospheric heating experiments were performed by ESSA of Boulder, Colorado, using the Platteville, Colorado, ionospheric heating transmitter (referred to in this report as the Boulder Heater). The HF pulse transmitting and receiving equipment, operated by Raytheon on a previous experiment at White Sands, was re-configured for backscatter sounding toward the heated region. The purpose was to directly illuminate the heated volume using two 100 Kw peak power pulse transmitters at different frequencies and to obtain both direct return and ground backscatter return echoes from the volume. The directly illuminating rays, when operating sufficiently high in frequency to avoid significant refractive bending in the ionosphere, perpendicularly intersect the earth's magnetic field lines at approximately 300 kilometer above the Boulder Heater. The perpendicular aspect geometry was considered important to obtain a detectable scattering cross-section from field aligned scatterers which may be underdense to the operating frequency for a 180° scattering angle. It was also of interest to obtain bending ray coverage in the heated volume which would be provided by ionospherically reflected one hop ground backscatter on a frequency which would place the backscatter skip distance at twice the Boulder range from White Sands.

(S) The pulse backscatter soundings were operated bistatically from the Paxton Siding transmitting site and Twin Buttes receiving site located south of Alamogordo, New Mexico at the eastern edge of the White Sands Missile Range.

SECRET

SECRET

(S) cont.

Both systems were operated from standard reference oscillators permitting coherent and synchronized transmission and reception. The antennas used for transmitting were log periodic beams horizontally oriented above ground and boresighted on a 7 degree true North bearing. Antennas at heights of 40 and 60 feet above ground were used at Paxton Siding to transmit the higher and lower frequencies respectively. At Twin Buttes, the receiving log periodic was at a 50 foot height and used throughout the tests for all frequencies. Maximum antenna gains ranging from 9 to 11 db over an isotropic radiator (including transmission line losses) and horizontal half power beamwidths of 65° are typically obtained with the log periodic arrays. The vertical elevation look angles of approximately 14.5° and 15.5° were considered optimum to illuminate the heated region from the White Sands sites for ordinary ray and extraordinary ray heating respectively. The corresponding range delays of 6.5 Ms (980 Km slant range) and 6.2 Ms (930 Km) were anticipated for direct returns for the two heating polarizations. For the ground backscatter returns, the operating frequencies were chosen to place the backscatter skip distance at approximately 1800 Km for ordinary ray and 1700 Km for extraordinary ray heating. A ground scattered return via the heated volume would therefore appear at the backscatter return leading edge with a range delay of 12 to 13 milliseconds or twice that of the direct return. Figure 1 shows the geometry profile for the White Sands Spread-F Experiment.

SECRET

SECRET




FIGURE 1

Geometry of the White Sands Spread-F Experiment
October 5-16, 1970 (U)

SECRET

SECRET

II. OBSERVATIONS AND RESULTS (U)

(S) During each of the six dates of heating experimentation several heating cycles were attempted as well as different heater frequencies and wave polarizations. The purpose was to test the effectiveness of the different techniques and to examine the time of day which yielded best results. Much of the data presented in this report is of a preliminary nature in order to view the results obtained at White Sands and to examine areas that need further exploration and analysis. Due to time limitations in making this data report available to the experimental and theoretical community most of the detailed explanations of the figures and processing technique are omitted at this time. A few points which should be noted in the figures, however, are presented in the following sections.

A. Backscatter Range Delay Versus Time Records (U)

(S) Figures 2 to 7 show the first 15 milliseconds of the pulse backscatter returns on the two frequencies transmitted from White Sands as a function of GMT for the 6 dates of experimentation. The receiver 15 KHz IF outputs were tape recorded in 45 minute segments. The data gaps in time are therefore attributable to either no data recording, equipment difficulties or frequencies of operation being changed. In Figure 2 on the 6th of October, a note is indicated where the pulse repetition frequency (PRF) was changed from 40 to 20 pulses per second. The return indicated at the 5 to 9 millisecond range delay prior to this time is not related to the Boulder heater cycle. This return is produced by 2 hop F region ground backscatter which overlaps the adjacent pulse period to which it should be associated (at 30 to 34 Ms). From this time on, a 20 pps repetition rate was utilized for the backscatter experiment

SECRET

SECRET

(S) cont.

thereby permitting a full 50 Ms of unambiguous time period between transmitted pulses. A transmitted pulse width of 500 microseconds was used for all tests except the 6th of October for which 100 microseconds was used.

(S) The transmission cycle of the Boulder heater is indicated at the top of each of the figures. For each day of operation except that of 6 October, the heater transmitting polarization was that of the ordinary ray. On the 6th of October the extra-ordinary mode was used. When both backscatter frequencies are shown, the upper record (higher frequency) and lower record can be cross examined for echoes, frequency dependence, and backscatter structure perturbations produced in the ionosphere. Some of these effects correlate directly and others last beyond the heating interval for periods ranging from minutes to perhaps an hour. Several of the obvious effects (but by no means all effects) have been selected for further processing to examine the echoes in more detail. In the following figures, the selected time intervals are analyzed particularly for received power, spectral power distribution, and characteristics within the scattered return.

B. Doppler Spectral Variation with Sample Depth (U)

(S) The records in Figures 8, 9 and 10 show how the integrated spectral shape changes with an increasing depth of sampling in the direct returns of 17 October 1970 (GMT date). These spectra are obtained with a total analysis frequency range of 10 Hz and a frequency resolution bandwidth of approximately 1/8 Hz. The records are obtained by sampling the coherently detected echo with narrow (40 microsecond) or "discrete" gates and processing the sampled (boxcar) waveform through a Federal Scientific UA-6A spectrum analyzer and digital averager. In general the spectrum shows a broadening with more power

SECRET

SECRET

(S) cont.

and hence provide "a selective skip distance shortening" phenomena for ray paths through the heated region (on the 13th and 17th of October). All of the four records were obtained on 13 MHz where ray bending would be anticipated in the heated region. The last ground backscattered echo on the 17th of October (Figure 17) differs from that obtained on the 13th of October (Figure 16), the range delay was only 9 Ms as opposed to 12 Ms. It is believed that this return is scattered from within the heated volume at an angle directly toward the earth below rather than obliquely to twice the range to Boulder. In this case the scattering at the earth is specular.

(S) It is interesting to compare the direct echo with the 9 Ms echo on the same frequency. The 9 Ms echo lasts to the end of the recording period in contrast to the 6 Ms direct echo (Figure 13). The spectral variations within the time period of heating correlate well between the two returns, however, the 9 Ms echo exhibits a more negative net Doppler shift. After the heating stops, the 9 Ms echo spectrum appears to stabilize. Finally the 9 Ms ground scattered echo exhibits an overall broader spectrum than that of the direct return.

(S) One further observation is worthy of note. The 12 Ms ground back-scattered return (via the heated region) on the 13th of October (Figure 15) exhibits the most diffuse spectral spread of any echo. The spectrum of this return spreads over the entire 10 Hz frequency range (one half the pulse repetition frequency) thereby making it impossible to estimate the total spectral width.

SECRET

SECRET

(S) cont.

at lower or negative Doppler frequencies as the sampling point moves further into the received pulse group. The spectrum obtained from the gate placed in the noise serves as a noise baseline for a reference.

C. Received Power and Spectral Variation with Time (U)

(S) Figures 11, 12 and 13 give an indication of how the received power of the echo changes or builds up with time. It should be noted that the ratio of the Boulder Heater frequency to local (ordinary ray) critical frequency approached unity at about 0220 GMT on Figures 12 and 13. The increased spectral spreading, therefore, is a function of the height (or depth) of heating within the ionosphere as both the 30 and 13 MHz echoes exhibited proportionate broadening.

(S) Several other interesting effects are noted in the Spectral data and power records of Figures 12 and 13. The net Doppler frequency shift of the return, which should be an indication of the ionospheric drift velocity, is proportionate to the operating frequencies. The shorter term (few minutes) cyclic variations in the spectrum during the heating cycle is correlated and proportionate on the two frequencies. Finally, the received power appears more than one order of magnitude larger on the 13 MHz frequency than on 30 MHz.

D. Power Spectrum of Additional Echoes (U)

(S) Four other selected returns have been analyzed and are shown in Figures 14 through 17. Two of these correspond to direct backscattered returns (at 6 Ms) obtained on the 6th and 13th of October. The other two are attributed to ground scattered returns which traverse the heated volume





SECRET

SECRET

E. Doppler Distribution Changes With Time (U)

(S) The final three records (Figures 18, 19 and 20) are included (from preliminary data reduction) to show one further interesting characteristic of the power spectra of the direct echoes (17th of October 1970). The peak spectral buildup with time throughout the heating interval appears to be accompanied by a spectral broadening. The spectral power density plots were obtained from consecutive 5 minute integration periods using a single discrete sample gate in the center of the direct echo. It appears that the spectrum becomes nearly flat topped as time progresses. The distribution of scatterer velocities, therefore, appears to widen as time progresses.

SECRET



SECRET

MENT NO. 1 - NIGHT - 6 OCTOBER 1970





Figure 2. Backscatter Range Delay Records from White Sands
Towards the Boulder Heated Region - 6 October 1970. (S

SECRET



SECRET

SPREAD F EXPERIMENT NO. 2 - DAY - 8 OCTOBER 1970





Figure 3. Backscatter Range Delay Records from White Sands Towards the Boulder Heated Region - 8 October 1970.(S)

SECRET

WHITE SANDS SPREAD F EXPERIMENT N



EXPERIMENT NO. 3 - MORNING - 9 OCTOBER 1970





Figure 4. Backscatter Range Delay Records from White Sands
Towards the Boulder Heated Region - 9 October 1970. (S)



SECRET

SPREAD F EXPERIMENT NO. 4 - NIGHT - 13 OCTOBER 1970





Figure 5. Backscatter Range Delay Records from White Sands
Towards the Boulder Heated Region - 13 October 1970(S)

SECRET



SECRET

EXPERIMENT NO. 5 - DAY - 15 OCTOBER 1970




Figure 6. Backscatter Range Delay Records from White Sands
Towards the Boulder Heated Region - 15 October 1970. (S)

SECRET




Figure 7.

SECRET

WHITE SANDS SPREAD F EXPERIMENT NO. 6 - NIGHT - 17 OCTOBER 1970




Figure 7. Backscatter Range Delay Records from White Sands
Towards the Boulder Heated Region - 17 October 1970. (S)

SECRET

UNCLASSIFIED




Figure 8. Integrated Power Spectrum at Discrete Range Delays in the 30 MHz Direct Backscatter Return on 17 October 1970 (0100 to 0120 GMT). (U)

UNCLASSIFIED




Figure 9. Integrated Power Spectrum at Discrete Range Delays in the 30 MHz Direct Backscatter Return on 17 October 1970 (0200 to 0220 GMT). (U)

UNCLASSIFIED




Figure 10. Integrated Power Spectrum at Discrete Range Delays in the 13 MHz Direct Backscatter Return on 17 October 1970 (0200 to 0220 GMT). (U)

UNCLASSIFIED

UNCLASSIFIED




Figure 11. Total Received Power Versus Time and Integrated Spectrum of the Direct Backscatter Return at 30 MHz on 17 October 1970 (0100 to 0120 GMT). (U)

UNCLASSIFIED




Figure 12. Total Received Power Versus Time and Integrated Spectrum of the Direct Backscatter Return at 30 MHz on 17 October 1970 (0200 to 0220 GMT). (U)




Figure 13. Total Received Power Versus Time and Integrated Spectrum of the Direct Backscatter Return at 13 MHz on 17 October 1970 (0200 to 0220 GMT). (U)

SECRET




Figure 14. Power Spectrum of the 13 MHz Direct Backscatter Returns from the Heated Region - 6 October 1970. (S)

SECRET

SECRET




Figure 15. Power Spectrum of a 13 MHz Direct Backscatter Return from the Heated Region - 13 October 1970. (S)

SECRET

SECRET




Figure 16. Power Spectrum of a 13 MHz Ground Backscatter Return (12 Ms) Supported by the Heated Region - 13 October 1970. (S)

SECRET

SECRET




Figure 17. Power Spectrum of a 13 MHz Specular Ground Backscatter Return (9 Ms) Supported by the Heated Region - 17 October 1970. (S)

SECRET

UNCLASSIFIED




Figure 18. Variation of Spectral Characteristics with Time at a Discrete Range Gate, 30 MHz - 17 October 1970 (0100 to 0120 GMT). (U)

UNCLASSIFIED




Figure 19. Variation of Spectral Characteristics with Time at a Discrete Range Gate, 30 MHz - 17 October 1970 (0200 to 0220 GMT). (U)




Figure 20. Variation of Spectral Characteristics with Time at a Discrete Range Gate, 13 MHz - 17 October 1970 (0200 to 0220 GMT). (U)

SECRET

III. THEORETICAL CONSIDERATIONS (U)

A. Scattering Cross-Section (U)

(S) A theory of scattering from field-aligned irregularities has been given by Booker⁽¹⁾ and applied to the problem of understanding the radar characteristics of auroral reflections. In view of the success of the theory in auroral situations and the apparent similarity of the irregularities produced by the Boulder heater (i.e., "Spread-F" on ionograms, direct echoes at oblique incidence when looking normal to the magnetic field), the Booker theory has been applied below to the geometry of the WSMR observations. In this way estimates of physical parameters such as irregularity scale sizes and mean electron density fluctuation can be derived from the radar observations.

(U) Booker shows that for a volume containing random irregularities having a Gaussian autocorrelation function the backscattered power is

$$\sigma_B = (2\pi)^{3/2} \pi^2 (1/\lambda_N)^4 \overline{(\Delta N/N)^2} T^2 L e^{-\left(\frac{8\pi^2 T^2}{\lambda^2}\right)} e^{-\left\{\frac{8\pi^2}{\lambda^2} (L^2 - T^2) \sin^2 \psi\right\}} \quad (1)$$

per unit volume, per unit solid angle, per unit incident power density, where

λ_N = wavelength corresponding to local electron plasma frequency

$\overline{(\Delta N/N)^2}$ = mean squared electron density fluctuation

T = fluctuation correlation distance transverse to magnetic field

L = fluctuation correlation distance along magnetic field

λ = radar wavelength

ψ = complement of angle between the direction of incidence and the axis of symmetry.

¹Booker, H. G., "A Theory of Scattering by Non-Isotropic Irregularities with Application to Radar Reflections from Aurora", J.A.T.P., 8, PP. 204 to 221, 1956.

SECRET

SECRET

(U) cont.

We want to integrate this backscattering coefficient over the volume containing irregularities in order to relate the measured radar cross-section to the physical properties of the scatterers.

(S) It can be shown that for the conditions of the present experiment,

$$\sigma = 4 \pi \int_V \sigma_B dv \quad (2)$$

where

σ = total radar cross-section

σ_B = volume scattering coefficient

V = the scattering volume contributing to the echo

We assume that the irregularities produced by the heater are contained in a cylinder of radius A aligned with the earth's magnetic field. The radius of the cylinder is taken to be the half-power radius of the heater beam. The cylinder is unbounded along the field. It may of course be that the irregularities do not in fact extend indefinitely along the field but this is probably unimportant since only those irregularities near the layer peak will contribute significantly to the observed signal. This is so because the intensity of the scatter depends on the square of the ambient electron density (and is therefore greatest at the peak) and because only those irregularities near the peak satisfy the specular conditions for radars located at WSMR. The geometry of the situation is shown in the sketch below:

SECRET

SECRET

(S) cont.




Figure 21. Scattering Geometry. (U)

We assume that $\overline{(\Delta N/N)^2}$, T , and L are constant throughout the volume but that λ_N and ψ vary along the cylinder (along the z -axis). The variation of $(1/\lambda_N)$ with z for a typical experiment is shown below (taken from an ESSA true-height electron density profile).




Figure 22. Variation of $(1/\lambda_N)$ Along Field Line. (U)

SECRET

SECRET

(S) cont.

In order to integrate σ_B analytically we model this curve as a Gaussian of the form

$$(1/\lambda_N) = (1/\lambda_{N_0}) e^{-(z^2/h^2)}$$

where

$$\lambda_{N_0} = \lambda_N \text{ at the layer peak } (z=0)$$

$$h = \text{Gaussian scale distance}$$

Finally, since $R \ll h$ we replace $\sin \psi$ with ψ and integrate σ_B to obtain

$$\sigma = \frac{8\sqrt{2} \pi^6 \lambda^2 (\Delta N/N)^2 T^2 L e^{-(8\pi^2 T^2/\lambda^2)}}{\lambda_{N_0}^4 \sqrt{(4/h^2) + 8\pi^2 (L^2 - T^2)/\lambda^2 R^2}} \quad (3)$$

B. Numerical Example

(S) As a numerical example we consider the measurements made just prior to heater turn-off during the last cycle on the night of 16 October 1970. The two radar frequencies in use at the time were 13.042 MHz (hereafter associated with subscript 1) and 29.764 MHz (hereafter associated with subscript 2). In tabular form,

$f_1 = 13.043 \text{ MHz}$	$f_2 = 29.764 \text{ MHz}$
$\lambda_1 = 23 \text{ m}$	$\lambda_2 = 10 \text{ m}$
$\sigma_1 = 1 \times 10^9 \text{ m}^2$	$\sigma_2 = 5 \times 10^7 \text{ m}^2$

and typically,

$L = 50 \text{ Km}$	(half the diameter of a 20° heater beam at 300 Km)
$h = 100 \text{ Km}$	(Gaussian half-width from Figure 3)
$\lambda_{N_0} = 57 \text{ m}$	(plasma wavelength from Figure 3)
$R = 900 \text{ Km}$	(range from WSMR to heated volume)

SECRET

SECRET

(S) Since there are three unknowns ($L, T, \overline{(\Delta N/N)^2}$) and only two observations (σ_1, σ_2) the unknowns can not be uniquely determined. However consider the special case in which the scatterers are isotropic so that $L = T$. Then equation (3) leads to

$$T^2 = \frac{\ln(\sigma_1/\sigma_2)}{8\pi^2(1/\lambda_2 - 1/\lambda_1)} \quad (4)$$

and

$$\overline{(\Delta N/N)^2} = \frac{\sigma_1 e^{+(8\pi^2 T^2/\lambda_1^2)}}{4\sqrt{2} \pi^6 h \lambda^2 (1/\lambda_{N_0})^4 T^3} \quad (5)$$

from which

$$T = 0.8 \text{ m}$$

and

$$\sqrt{\overline{(\Delta N/N)^2}} = 0.12$$

That is, in order to explain the observations on the basis of irregularities which are not field aligned, the scatterers would have to

- a.) fill a cylindrical volume roughly 100 Km in diameter and 100 Km long
- b.) have a correlation distance of about 0.8 meters
- c.) have a root-mean-square electron density fluctuation of about 12%.

It is not obvious that these are unreasonable requirements and consequently it is perhaps premature to conclude that the WSMR observations demonstrate the existence of field-aligned scatterers in the heated volume. On the other hand, the observations could be more easily explained (smaller scattering volume and weaker mean electron density fluctuations) if the irregularities were in

SECRET

SECRET

(S) cont.

fact field aligned (L>>T). Additional measurements will be needed to settle the question.

SECRET

SECRET

IV. SUMMARY AND CONCLUSIONS (U)

(S) The WSMR series of experiments was designed primarily as a test of the hypothesis that ionospheric irregularities generated by the Boulder heater would produce detectable radar returns at frequencies well above the maximum ionospheric plasma frequency when viewed normal to the magnetic field.

1. The result of this test is positive: direct echoes from the heated volume have unquestionably been observed at frequencies up to 30 MHz (the highest available during the test series) at times when the maximum ionospheric plasma frequency was about 5 MHz.
2. The results vary widely from day to day and from heating cycle to heating cycle on the same day. Some days no echoes at all were detected while other days targets as large as 10^9 m^2 were observed. The following possible explanations are offered for this behavior:
 - a. It may be that irregularities are generated only near the reflection height of the heater and are strongly field aligned. They would then be highly aspect sensitive and echoes would be observed at WSMR only if the reflection height of the heating signal were near the specular point for WSMR, i.e., near 290 Km. Since this height is also near the layer peak it implies that the heater would have to be operating near the critical frequency of the layer.

SECRET

SECRET

(S) cont.

In this case when the heater was operated well below the critical frequency for the layer, the scatterers would lie well below the specular point for WSMR and could not be observed due to aspect sensitivity. They could be observed, however, by a radar further north than WSMR for which the specular point would be lower in altitude.

- b. It may be that irregularities strong enough to support direct backscatter are only produced when the heater operates near the critical frequency of the layer. In this case aspect sensitivity is not required to explain the absence of echoes at WSMR and direct echoes would not be observed from any location when the heater was operating well below the critical frequency of the layer.
 - c. It may be that refraction of the radar rays from WSMR to the heated volume is great enough and variable enough to explain the absence of echoes when coupled with high aspect sensitivity and/or variable height of generation.
 - d. It may be that ambient geophysical conditions (such as magnetic activity) make the ionosphere prone to irregularity generation on some days and not on others.
3. The direct radar returns occur at the range to the heated volume and turn on and off with the heater. The echo strength builds up steadily during the 20 minutes of heating. At 30 MHz the echo disappears after heater turn-off in about 10 seconds while at 13 MHz the echo disappears after about 100 seconds. The longer

SECRET

SECRET

(S) cont.

persistence of the lower frequency echo may be a consequence of the larger irregularity scale responsible for this return and the correspondingly longer time required for diffusion to smooth these fluctuations out.

At 30 MHz the doppler spectrum of the return is typically spread by a few hertz and has a net positive doppler shift of a few hertz. This is tentatively interpreted as implying a differential velocity between scatterers and a net southward drift of scatterers of a few tens of meters per second.

4. It has not been demonstrated that the irregularities responsible for the radar returns are field aligned. However in order to explain the strength and wavelength dependence of the echoes on the basis of isotropic scatterers, they would have to
 - a. occupy a cylindrical volume about 100 Km in diameter and 100 Km long,
 - b. have a Gaussian correlation function with a scale size of 0.8 meters,
 - c. have a root-mean-square electron density fluctuation of 12%.

While these requirements are not impossibly severe, the results could be explained by weaker scatterers in a smaller volume if the irregularities were field aligned.

SECRET

SECRET

(S) cont.

5. In addition to the direct returns there are also perturbations observed in the ground backscatter returning through the heated volume. These have received little study as yet.

SECRET

SECRET

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Raytheon Company Sudbury Laboratories Sudbury MA 01776		2a. REPORT SECURITY CLASSIFICATION SECRET	
		2b. GROUP 3	
3. REPORT TITLE HF BACKSCATTER ECHOES FROM WHITE SANDS SPREAD F EXPERIMENT (U)			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Interim Report			
5. AUTHOR(S) (First name, middle initial, last name) Dr. George D. Thome Mr. David W. Blood			
6. REPORT DATE December 1970		7a. TOTAL NO. OF PAGES 38	7b. NO. OF REFS 0
8a. CONTRACT OR GRANT NO. F30602-68-C-0299		9a. ORIGINATOR'S REPORT NUMBER(S)	
b. PROJECT NO. 1423			
c.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.		RADC-TR-71-15	
10. DISTRIBUTION STATEMENT In addition to security requirements which must be met, this document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of ARPA/STO, Arlington VA 22209			
11. SUPPLEMENTARY NOTES Monitored By Joseph J. Simons RADC/OCSE/GAFB, NY 13440 AC 315-330-3451		12. SPONSORING MILITARY ACTIVITY Advanced Research Projects Agency Arlington, VA 22209	

13. ABSTRACT

SECRET ABSTRACT

(S) The results of direct HF backscatter echoes from six White Sands F Experiment are presented. The Spread F type conditions result from the heating of the F layer of the ionosphere through the utilization of a high power transmitter near Boulder, Colorado. Direct echoes from the heated volume were observed at frequencies as high as 30 MHz and were well correlated with the turn-on and turn-off of the Boulder transmitter.

SECRET

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Ionosphere Spread F HF Backscatter						

SECRET

Security Classification